




10K PI

Diagnostic Insulation Tester



10K PI is an Insulation Diagnostic Tester having test voltage range up to 10KV, designed & developed indigenously at the state of the art R&D laboratory to conduct automatic insulation tests on high voltage equipment's like Transformers, Cables, Bushings, Switchgears & Rotating Machines. 10KPI comes in two ranges of short circuit current of 3mA and 6mA. 10K PI is a microprocessor based instrument deploying the latest technology & very high speed data sampling to give correct, repetitive readings & quality performance under harsh electrical conditions. It has a wide insulation resistance range up to 50TΩ.

Model 10K PI is mains and battery operated portable & compact insulation tester for outdoor applications. The battery backup of 8 Hours makes it suitable for field operations. IP 65 rating keeps 10K PI safe from water & dust ingress. It complies with CAT IV 600V for safe operation. The instruments & its accessories are certified as per relevant IS/IEC standard.

The Information displayed on the large backlit LCD includes insulation resistance, leakage current, capacitance, battery status & timer. Three programmable timers are provided to conduct various tests like Polarization Index (PI), Dielectric Absorption Ratio (DAR), Dielectric Discharge (DD), Step Voltage (SV), & Breakdown Voltage (BDV) Test. 10K PI can store up to 1000 test results*. PC interface via USB & RS-232 for data transfer. The PC software for report generation & data trending analysis helps to keep records of capital equipment. Instrument has automatic discharge facility for capacitive loads discharging. The instrument has the automatic discharge facility for capacitive load discharge at the end of the test.

Features

- ✓ 10K PI available in two variants : 3mA, 6mA
- ✓ IR Testing with Diagnostic Modes PI, DAR, DD, SV, BDV, Burn.
- ✓ Programmable Test Voltage: 250V, 500V, 1000V, 2500V, 5000V, 7500V, 10000V
- ✓ Insulation Resistance Range from 10KΩ to 50TΩ
- ✓ Three Programmable Timers: T1, T2, T3 respectively
- ✓ Programmable Break Down Current Settings
- ✓ Mains & Battery operation
- ✓ Internal Data Storage up to 1000 tests*
- ✓ Galvanic Isolated RS 232 & USB Port
- ✓ Application Software for Data Trending Analysis
- ✓ AC/DC voltage measurement up to 600V
- ✓ Auto Calibration at every start up
- ✓ Burn Mode for uninterrupted Insulation Resistance Testing
- ✓ Alarm Mode with Min-Max Settings & Pass Fail Indication
- ✓ CAT IV 600V, IP 65, Complies with latest IEC/IS Standards
- ✓ Operation from an AC source when the battery is flat
- ✓ Digital filter is designed with three different levels F-1, F-2, F-3 useful while testing insulation in heavy noisy environment.
- ✓ For 10K PI 6mA, Interference Rejection: 1mA RMS per 250V test voltage up to a max. of 8mA

Applications

The Insulation Resistance Test is an essential test that helps to verify the condition of electrical insulation. Insulation resistance quality of an electrical system degrades with time, environment condition i.e. temperature, humidity, moisture and dust particles. The instrument is designed for routine insulation resistance testing and diagnostic testing like PI, DD, DAR & SV of high voltage electric apparatus like transformers, generators, motors, cables, bushings, LAs, switchgear, etc. and is temperature independent. It can be operated in 220 kV, 400 kV and 765 kV* switchyards. Trending of data can reveal vital information about insulation quality and enables the user to take informed decision.

* Applicable for 10K PI 6mA only

SPECIFICATIONS		10K PI	
	10K PI 3mA	10K PI 6mA	
Test Specifications			
Diagnostic Modes	IR, PI, DAR, DD, SV, BDV, Burn		
Test Voltage			
Programmable Test Voltage	250V, 500V, 1000V, 2500V, 5000V, 7500V, 10000V		
Lock Test Voltage	250 - 1000V adjustable in steps of 10V, 1000 - 10000V adjustable in steps of 25V		
Voltage Accuracy	± (5% of reading + 5 digits)		
Resistance Range			
Analog Display	10KΩ - 10TΩ	10KΩ - 10TΩ	
Digital Display	10KΩ - 20TΩ	10KΩ - 50TΩ	
Accuracy	1 MΩ to 1 TΩ ± (5% of reading + 5 digits)	1 MΩ to 1 TΩ ± (5% of reading + 5 digits)	
	1 TΩ to 10 TΩ ± (10% of reading + 5 digits)	1 TΩ to 10 TΩ ± (10% of reading + 5 digits)	
	10 TΩ to 20 TΩ ± (20% of reading + 7 digits)	10 TΩ to 50 TΩ ± (20% of reading + 7 digits)	
Guard Resistance	2% error guarding <300KΩ		
Short Circuit/Charge Current			
Current Range	up to 3mA	up to 6mA	
AC/DC Voltage			
Voltmeter Range	0 - 600 AC/DC		
Voltmeter Accuracy	±(8% of reading + 5 digits), input resistance: 250MΩ Approx		
Capacitance Measurement			
Capacitor Discharge Time	≤ 5 sec per μF		
Capacitance Range	1nF to 50μF		
Capacitance Measurement Accuracy	± (5% of readings + 5 nF)		
Interference Rejection	1mA RMS per 250V test voltage up to a max. of 5mA	1mA RMS per 250V test voltage up to a max. of 8mA	
Timer			
	Programmable timer from 0 sec to 99 minutes		
Memory			
	Internal data storage of 1000 readings		
Interface			
	Galvanically isolated RS232 and USB ports; remote operation via PC using either RS232 or USB cable		

SPECIFICATIONS

10K PI

10K PI 3mA

10K PI 6mA

Data Handling & Analysis Software

Operated on XP/Windows7/Windows8/Windows10/Windows11

Two way communication for remote operation

Report generation along with the graphical representation for Data Trending Analysis.

Power Supply

Mains Input Voltage

115V/230V RMS \pm 10%, Frequency 50/60 Hz

Battery Type

Battery Pack, Rechargeable 14.8V, 5200mAh, Li-Ion, Type 18650

Battery Life

8 hours continuous testing at 10kV with a 250 M Ω load (approx)

Battery Charge Time

8 hours approx. (95% Charged)

Auto Power Off

Instrument turns off after 10 minutes of non-use to conserve battery life

Environmental Condition

Operating Temperature Range

-10°C to 55°C

Storage Temperature Range

-20°C to + 70°C.

Humidity

< 95% RH Non-Condensing

Safety

Safety in accordance with EN61010-1

EMC in accordance with EN61326-1

Type test in accordance with IEC 60068

Test lead in accordance with IEC 61010-31

CE & CAT III 1000V & IV 600V, IP 65

Physical Specifications

Dimensions

190 mm X 285 mm X 365 mm (Approx.) (H x W x L)

Weight

5 Kg (approx) (without accessories)

9.5 Kg (approx) (with accessories)

Accessories

Standard

■ 3m Test lead Set (3mA)	: 1 Set
■ 10m Test lead Set (6mA)	: 1 Set
■ Mains Power Cord	: 1 Set
■ Mains Protected Fuse	: 2 No.
■ RS232 Communication cable	: 1 No.
■ Instruction Manual	: 1 No.
■ Calibration Certificate	: 1 No.
■ Carry Case	: 1 No.
■ Pen Drive	: 1 No.
■ USB 2.0 A/B Cable 1.5 mtr long	: 1 No.

Optional

■ 15m Test lead Set	: 1 Set
---------------------	---------

ORDERING INFORMATION

Product

Order Code

10K PI 3mA

109385010

10K PI 6mA

1096AD010

with Standard Accessories